

## ULTRA PREMIUM

JUNE 2016

## OIL BASED STAIN BLOCKER

PAGE 1 OF 3



### Description

Valspar Ultra Premium Preps are designed to make your painting project a more positive experience. Let Valspar help you create a space you can't wait to get home to.

Valspar Oil based Stain Blocker prepares your surface for your new colour whilst ensuring optimal performance of your top coat. This product provides superior stain blocking performance against water soluble staining contaminants. It is ideal for locking in stubborn smoke, water, tannin bleed on interior timber. May be used under both water and oil based finish coats

### Why Valspar?

- |  |   |
|--|---|
| <ul style="list-style-type: none"> <li>Interior &amp; Exterior Surfaces</li> <li>Superior blocking for water based stains</li> </ul> | <ul style="list-style-type: none"> <li>Blocks nicotine and smoke stains</li> <li>Use with water and oil based topcoats</li> </ul> |
|--|---|

### Colours

White

Must be top coated.

### Properties & Performance Guide

Dry & Recoat Times	Touch Dry - 4 hours Recoat - 24 hours Fully Cured - 7 days Figures are quoted at 25°C and at 50% humidity. Drying will take longer at lower temperatures or higher relative humidity.
Coverage per Coat	Up to 14 M <sup>2</sup> /L depending on the surface texture, porosity and method of application.
Thinning	Do not thin this product.
Clean Up	Clean up with mineral turps away from drains. <b>Protect Our Environment:</b> Do not pour leftover paint down the drain. Unwanted paint should be kept in a sealed container, and then disposed of via special waste collection services. Empty paint containers should be left open in a well ventilated area to dry out. Disposal of empty paint containers may differ between local authorities. Check with your local council first.
VOC (Volatile Organic Compounds)	VOC < 420 g/Litre.

# ULTRA PREMIUM

JUNE 2016

# OIL BASED STAIN BLOCKER

PAGE 2 OF 3

## Before Painting

Read safety information below before painting.

- All surfaces must be clean, dry and free of dirt, chalk, grease and grime. Remove residual stains from with a household cleaner and rinse clean.
- Remove old, loose or flaking paint. Sand chalky paint until sound.
- Valspar Oil Based Stain Sealer will tolerate residual chalk or kalsomine.
- Sand enamel painted surfaces until gloss is removed.
- Test soundness of previously painted surfaces. Unsound surfaces should be stripped.
- Remove all mould with a household bleach solution. Rinse thoroughly with clean water. Valspar Oil Based Stain Blocker will seal residual stains but will not prevent active mould growth.
- Sand bare timber smooth and remove all mill glaze.
- Allow fresh cement & concrete surfaces to fully cure; typically a 4-6 week period.

## Application & After Painting

- Apply when the air and surface temperatures are above 10°C and below 35°C.
- Stir contents before use with a broad paddle to ensure paint is thoroughly mixed.
- Apply full, even coats using a premium quality brush or roller, or spray.
- Do not thin this product.

### AFTER PAINTING

- Remove as much paint as possible from brushes and rollers before cleaning up in mineral turps away from drains.
- Wipe up spills immediately with a damp cloth.
- **Soak all contaminated cloths in water after use as they may self ignite.**

## Usage Areas

Stain Type	Valspar WB Stain Blocker	Valspar OB Stain Blocker	Valspar Spirit Based Stain Blocker <sup>1</sup>
Water Stains	✓	✓✓✓	✓✓✓
Mould <sup>2</sup>	✓	✓✓✓	✓✓✓
Tannin Bleed	✓✓ <sup>3</sup>	✓✓✓	✓✓
Nicotine/Tobacco	✓	✓✓✓	✓
Smoke	✓	✓✓✓	✓✓✓
Pencil	✓✓✓	✓✓✓	✓✓
Crayon	✓✓✓	✓	✓✓
Marker	✓✓	✓✓	✓✓
Lipstick	✓✓✓	✓✓	✓✓✓
Cooking	✓✓✓	x	✓✓✓
Oil/Grease	✓✓✓	x	✓✓✓
Bitumen	✓✓	x	✓✓✓
Timber Dye Stains	✓	✓✓✓	x
Pet Stains	x	✓✓✓	✓✓✓
Odour Sealing	x	✓✓	✓✓✓

<sup>1</sup> For interior use only.

<sup>2</sup> Primer will seal residual stains but will not prevent active mould growth. Remove all mould with a solution of 1 part household bleach and 3 parts water. Rinse thoroughly with clean water.

<sup>3</sup> For best tannin bleed resistance allow to dry overnight before applying finish coats.

# ULTRA PREMIUM

JUNE 2016

# OIL BASED STAIN BLOCKER

PAGE 3 OF 3

## Additional Data

Available in 4 and 10 litre containers.  
Containers must be secured and stored upright during transit.  
Containers must not be exposed to excessive heat or cold.  
The use of proprietary additives other than those manufactured by Valspar is not recommended.

## Safety Data

<p><b>General First Aid Instructions</b></p>	<p>For advice, contact the Poisons Information Centre on 131 126 (Aust), 0800 764 766 (NZ) or a doctor. If swallowed, do not induce vomiting. Give a glass of water to drink. If in eyes, wash out immediately with water. If inhaled, remove from contaminated area to fresh air. If skin contact occurs, remove contaminated clothing and flush contaminated skin with water.</p>
<p><b>General Safety Directions</b></p>	<p>HAZARDOUS - Contains 30-60% liquid hydrocarbons. Flammable. Keep away from sources of ignition. No smoking. Keep closed when not in use. Keep out of reach of children. Irritating to skin and eyes. Avoid contact with skin and eyes - wear suitable protective clothing. Avoid prolonged breathing of vapour. Wash hands thoroughly after use. PROVIDE ADEQUATE VENTILATION DURING USE.</p>
<p><b>Further Information</b></p>	<p>For the latest information refer to the Safety Data Sheet available on our website or contact Valspar Customer Service. <b>Australia</b> Phone: 132 101 Web: <a href="http://www.valspar.com.au">www.valspar.com.au</a> <b>New Zealand</b> Phone: 0800 825 7727 Web: <a href="http://www.valsparpaint.nz">www.valsparpaint.nz</a></p>

- This information is provided with respect to the listed Valspar products. Valspar Paint (Australia) recommends that:
  - You review the Technical Data Sheets (TDS) and Safety Data Sheets (SDS) before you use or handle the product;
  - the product be used only in accordance with the information provided by Valspar;
  - the product be transported and handled in accordance with the SDS and relevant TDS; and
  - you thoroughly test the product, using the recommended application method on a sample of intended substrate, before using the product.
- The information in the technical data sheet was prepared using information gathered during product development. While Valspar endeavours to update this information and maintain the accuracy of its contents, Valspar cannot guarantee that the information is wholly comprehensive.
- Valspar recommends that you conduct such additional investigations as may be necessary to satisfy yourself of the accuracy, currency and comprehensiveness of the information on which you rely in using and handling the product. If you require further information please contact your nearest Valspar Office.
- To the full extent permitted by law, Valspar's liability for breach of a condition or warranty implied into the contract for sale between Valspar and you by law is limited at Valspar's election to: (a) the replacement of the product; or (b) payment of the cost of replacing the product.

Valspar is a registered trademark of The Valspar Corporation, USA

VALSPAR CUSTOMER SERVICE: Ph: 132 101 (AUSTRALIA) – Ph: 0800 825 7727 (NEW ZEALAND)