


DECK & TIMBER CLEANER BRIGHTENER

MARCH 2018

PAGE 1 OF 2



DESCRIPTION

Valspar Deck & Timber Cleaner Brightener is easy to use and highly effective for cleaning and preparing new and old exterior timber. Being an Oxalic acid, citric acid and detergent based timber cleaner, it is designed to rejuvenate and clean greying timber, or remove mould, surface grime, dirt, or naturally occurring tannins from new timber, before coating with an oil, stain, varnish or paint.

WHY VALSPAR?

- Rejuvenates greying timber
- Removes dirt and grime
- Removes mould
- Water based
- Easy to use
- Prepares timber for coating

COLOUR

Clear

PROPERTIES

Coverage 4 to 8 m² /L when diluted.

Clean Up Clean equipment with water away from drains.

USAGE AREAS

Exterior wood work such as decks, outdoor furniture, barbeque trolleys, window frames, gates, weatherboards etc

BEFORE USING

Read safety information below before using.

- Wear gloves and eye protection when using this product.
- NOTE:** Avoid contact with paints, sealants, metal surfaces or vegetation; cover before use and rinse off immediately if contact occurs.
- Remove loose dirt and debris from timber with a broom or brush.

APPLICATION:

- Mix one part of Valspar Deck & Timber Cleaner Brightener to four parts water in a plastic container. For major staining or discolouration, a stronger or repeat application may be required.
- Wet the surface to be cleaned thoroughly with water prior to application.
- Apply a generous coat of the solution and scrub into the timber with a stiff bristle brush or broom. Do not use a wire brush.
- Leave the solution on the timber for 10-20 minutes.
- Wash the surface thoroughly with a garden hose or scrub with fresh water then rinse.
- If mould is still present, a further treatment with household bleach and water is recommended. Ensure cleaner has been rinsed off totally before applying bleach.
- Rinse entire timber surface thoroughly with clean water.
- Clean equipment with water.
- Allow the timber to dry thoroughly before applying oil, stain, varnish or paint. This may take up to 48 hours in dry weather.

**DECK & TIMBER CLEANER
BRIGHTENER**

RESOURCE CODE 516441

MARCH 2018

PAGE 2 OF 2

WARNING: Rinse off within 20 minutes. Failure to completely remove Oxalic acid solutions may result in timber discolouration under clear timber finishes.

Not for interior use. Do not use on previously painted, varnished or non-timber surfaces such as sealants or metal.

ADDITIONAL DATA:

Available in 1L& 4L containers.

Containers must be secured and stored upright during transit.

Containers must not be exposed to excessive heat or cold. Do not store containers in areas susceptible to frost.

SAFETY DATA:**• Warning:****Corrosive**

Contains Oxalic Acid 80g/L, Citric Acid 25g/L, Quaternary Ammonium Compound 25g/L (as active).

Avoid contact with metal, painted surfaces and vegetation. Rinse off within 30 minutes. Failure to completely remove oxalic acid solutions may result in timber discolouration under clear finishes.

Spills and disposal:

Do not allow spilt material to enter drains or other watercourses. Absorb spills with sand or other inert material. Do not pour leftover product down the drain. Unwanted product should be kept in a sealed container, and disposed of via special waste collection services.

SDS:

A Safety Data Sheet (S.D.S.) is available on the website or contact 0800 825 7727.

First Aid:

If swallowed **do not** induce vomiting. Give plenty of water to drink. Contact a doctor or the Poisons Information Centre. Phone 0800 764766. If in eyes, hold eyes open and flood with water for at least 15 minutes. Contact a doctor if any irritation occurs. If on skin remove contaminated clothing, wash skin thoroughly with soap and water or a proprietary skin cleanser. Do not use solvents. If affected by inhalation remove person to fresh air. If breathing difficulties persist or occur later, contact a doctor.

1. This information is provided with respect to the listed Valspar products. Valspar recommends that:
(a) The user should check the date of printing, and if more than 24 months have elapsed, should verify with our nearest sales office that the information is still current; (b) you review the Technical Data Sheets (TDS) and Safety Data Sheets (SDS) before you use or handle the product; (c) the product be used only in accordance with the information provided by Valspar; (d) the product be transported, stored and handled in accordance with the information on the SDS and relevant TDS; and (e) you thoroughly test the product, using the recommended application method on a sample of intended substrate, before using the product.
2. The information in this technical data sheet was prepared using information gathered during product development. While Valspar endeavours to update this information and maintain the accuracy and currency of its contents, Valspar cannot guarantee that the information provided is wholly comprehensive.
3. Valspar recommends that you conduct such additional investigations as may be necessary to satisfy yourself of the accuracy, currency and comprehensiveness of the information on which you rely in using and handling the product. If you require further information please contact your nearest Valspar Office.
4. Because we cannot control the way these products may be used, or the conditions they may be exposed to, we can give no express guarantees in respect of these products or their performance. However certain guarantees may be implied by law.
Valspar Paint (NZ) Ltd, PO Box 1545, Shortland St, Auckland 1140 Phone 09 820 6700 For product advice & assistance call toll free 0800 825 7727